


All-Purpose Module

RS6E-80P is a robust solar module with 36 solar cells. These modules can be used for on-grid solar applications. Our meticulous design and production techniques ensure a high-yield, long-term performance for every module produced. Our rigorous quality control and in-house testing facilities guarantee Resun Solar's modules meet the highest quality standards possible.



Monocrystalline Silicon Solar Modules

Features



High module conversion efficiency (up to 15.6%), through superior manufacturing technology



Guaranteed 0- +5W positive power output tolerance ensures high reliability



Anti-reflective, hydrophobic coating improves light absorption and reduces surface dust



Excellent performance under low light environments (mornings, evenings and cloudy days)



Entire module certified to withstand high wind loads (2400 Pascal) and snow loads (5400 Pascal)*




All-purpose Module

Sales network covers more than 20 countries, providing customers with instant after sales service and an efficient supply-chain, our clients can be found throughout the world, such as North America, Europe, Oceania, Eastern Europe, East Asia, Middle Easter and Africa etc. Resun Solar team works closely with our customers to provide them with solutions for all their solar needs.




Resun reputation is founded on more than 200MW of high performance solar modules installed around the world.

Industry-leading warranty



- 25 year transferable power output warranty:10year/90%;25year/80%.
- Based on nominal power.
- 10 year material and workmanship warranty.

RS6E- 80P




Electrical Data

STC	RS6E-80P
Nominal Maximum Power(Pmax)	80W
Optimum Operating Voltage(Vmp)	19.8V
Optimum Operating Current(Imp)	4.05A
Open CIRCUIT voltage(Voc)	23.96V
Short Circuit Current(Isc)	4.05A
Operating Temperature	-40°C~+85°C
Maximum System Voltage	1000V(IEC)/600V(UL)
Maximum Series Fuse Rating	10A
Application Classification	Class A
Power Tolerance	0 ~ + 5W

Mechanical Data

Cell Type	Poly-crystalline 156 x 156mm, 5 Bus bars
Cell Arrangement	36(4x9)
Dimensions	860*670*30MM
Weight	7kg
Front Cover	3.2mm Tempered Glass
Frame Material	Anodized Aluminum Alloy
J-BOX	IP67
Cable	2.5mm2(IEC)/12AWG(UL), 1150mm
Connectors	MC4 or MC4 Comparable
Standard Packaging (Modules per Pallet)	50pcs
Module Pieces per container (40HQ)	850pcs (40'HQ)



Temperature Characteristics

Nominal Operating Cell Temperature (NOCT)	45±2°C
Temperature Coefficient of Pmax	-0.43%/°C
Temperature Coefficient of Voc	-0.34%/°C
Temperature Coefficient of Isc	0.065%/°C

Packing Configuration

Container	20'GP	40'HQ
Pieces	380	850

Resun Solar Energy Co.,Ltd

Tel:3003973502

E-mail:comercial@improinde.com